

Underdesk power module - Type G UPMA-2P



Features

Install in cable trays or fix to the underside of the desk with brackets or velcro pads provided

2 x Type G (UK) 5A* individually fused power socket

1 x male + 1 x female GST 3-pole connector

1 - 10m metre mains power cables available with 13A Type G (UK) plug to GST 3-pole female connector

1 or 2 metre connector cable available with male to female GST 3-pole connectors

250mm trailing earth wire

Champagne alloy case with black plastic insert

| Module Dimensions | W223 x D52 x H48 mm |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| Capacitities | Type G (UK) power sockets: 250V x max. 5A* |
| Weight | 0.37kg |
| Materials | Alloy case, plastic insert |
| Warranty | 5 years |
| Certification | Fully tested / certified to BS 5733 & BS 1363-2, CE marked (meets BS 6396 requirements) |
| Boxed Dimensions | W280 x D70 x H60 mm |
| Boxed Weight | 0.41kg |
| Outer Box Dimensions - 20 units | W330 x D300 x H310 mm |
| Outer Box Weight | 8.6kg |
| * Powerlink power modules up to 4 sockets come with 3.15amp fuses fitted as standard. On installations of 4 sockets or less we can upgrade fuses to 5amp if required. | |







Underdesk power module - Type G UPMA-2P1N



Features

Install in cable trays or fix to the underside of the desk with brackets or velcro pads provided

2 x Type G (UK) 5A* individually fused power socket

1 x red neon master switch

1 x male + 1 x female GST 3-pole connector

1 - 10m metre mains power cables available with 13A Type G (UK) plug to GST 3-pole female connector

1 or 2 metre connector cable available with male to female GST 3-pole connectors

250mm trailing earth wire

Champagne alloy case with black plastic insert

Plastic free packaging

| Module Dimensions | W266 x D52 x H48 mm |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| Capacitities | Type G (UK) power sockets: 250V x max. 5A* |
| Weight | 0.41kg |
| Materials | Alloy case, plastic insert |
| Warranty | 5 years |
| Certification | Fully tested / certified to BS 5733 & BS 1363-2, CE marked (meets BS 6396 requirements) |
| Boxed Dimensions | W320 x D70 x H60 mm |
| Boxed Weight | 0.46kg |
| Outer Box Dimensions - 20 units | W340 x D330 x H310 mm |
| Outer Box Weight | 9.5kg |
| * Powerlink nower modules up to 4 sockets come with 215amp fuses fitted as standard. On installations of 4 sockets or loss we can upgrade fuses to 5amp if required | |

* Powerlink power modules up to 4 sockets come with 3.15amp fuses fitted as standard. On installations of 4 sockets or less we can upgrade fuses to 5amp if required.







Underdesk power module - Type G UPMA-3P



Features

Install in cable trays or fix to the underside of the desk with brackets or velcro pads provided

3 x Type G (UK) 5A* individually fused power socket

1 x male + 1 x female GST 3-pole connector

1 - 10m metre mains power cables available with 13A Type G (UK) plug to GST 3-pole female connector

1 or 2 metre connector cable available with male to female GST 3-pole connectors

250mm trailing earth wire

Champagne alloy case with black plastic insert

| Module Dimensions | W264 x D52 x H48 mm |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| Capacitities | Type G (UK) power sockets: 250V x max. 5A* |
| Weight | 0.44kg |
| Materials | Alloy case, plastic insert |
| Warranty | 5 years |
| Certification | Fully tested / certified to BS 5733 & BS 1363-2, CE marked (meets BS 6396 requirements) |
| Boxed Dimensions | W320 x D70 x H60 mm |
| Boxed Weight | 0.49kg |
| Outer Box Dimensions - 20 units | W340 x D330 x H310 mm |
| Outer Box Weight | 10.3kg |
| * Powerlink power modules up to 4 sockets come with 3.15amp fuses fitted as standard. On installations of 4 sockets or less we can upgrade fuses to 5amp if required. | |







Underdesk power module - Type G UPMA-4P



Features

Install in cable trays or fix to the underside of the desk with brackets or velcro pads provided

4 x Type G (UK) 5A* individually fused power socket

1 x male + 1 x female GST 3-pole connector

1 - 10m metre mains power cables available with 13A Type G (UK) plug to GST 3-pole female connector

1 or 2 metre connector cable available with male to female GST 3-pole connectors

250mm trailing earth wire

Champagne alloy case with black plastic insert

Plastic free packaging

| Module Dimensions | W327 x D52 x H48 mm |
|------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Capacitities | Type G (UK) power sockets: 250V x max. 5A* |
| Weight | 0.5kg |
| Materials | Alloy case, plastic insert |
| Warranty | 5 years |
| Certification | Fully tested / certified to BS 5733 & BS 1363-2, CE marked (meets BS 6396 requirements) |
| Boxed Dimensions | W360 x D70 x H60 mm |
| Boxed Weight | 0.55kg |
| Outer Box Dimensions - 20 units | W380 x D330 x H310 mm |
| Outer Box Weight | 11.2kg |
| * Powerlink nower modules up to A sockets come | with 315 mm fuses fitted as standard. On installations of A sockets or less we can ungrade fuses to 5 mm if required |

* Powerlink power modules up to 4 sockets come with 3.15amp fuses fitted as standard. On installations of 4 sockets or less we can upgrade fuses to 5amp if required.







Underdesk power module - Type G UPMA-4P1N



Features

Install in cable trays or fix to the underside of the desk with brackets or velcro pads provided

4 x Type G (UK) 5A* individually fused power socket

1 x red neon master switch

1 x male + 1 x female GST 3-pole connector

1 - 10m metre mains power cables available with 13A Type G (UK) plug to GST 3-pole female connector

1 or 2 metre connector cable available with male to female GST 3-pole connectors

250mm trailing earth wire

Champagne alloy case with black plastic insert

Plastic free packaging

| Module Dimensions | W370 x D52 x H48 mm |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| Capacitities | Type G (UK) power sockets: 250V x max. 5A* |
| Weight | 0.53kg |
| Materials | Alloy case, plastic insert |
| Warranty | 5 years |
| Certification | Fully tested / certified to BS 5733 & BS 1363-2, CE marked (meets BS 6396 requirements) |
| Boxed Dimensions | W420 x D70 x H60 mm |
| Boxed Weight | 0.59kg |
| Outer Box Dimensions - 20 units | W440 x D310 x H180 mm |
| Outer Box Weight | 12kg |
| * Powerlink power modules up to 4 sockets come with 3.15amp fuses fitted as standard. On installations of 4 sockets or less we can upgrade fuses to 5amp if required. | |

Powerlink power modules up to 4 sockets come with 3.15amp fuses ritted as standard. On installations of 4 sockets or less we can upgrade fuses to 5amp if required.







Underdesk power module - Type G UPMA-6P



Features

Install in cable trays or fix to the underside of the desk with brackets or velcro pads provided

6 x Type G (UK) 3.15A individually fused power sockets*

1x male GST 3-pole connector*

1 - 10m metre mains power cables available with 13A Type G (UK) plug to GST 3-pole female connector

1 or 2 metre connector cable available with male to female GST 3-pole connectors

250mm trailing earth wire

Champagne alloy case with black plastic insert

| Module Dimensions | W388 x D52 x H48 mm |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| Capacitities | Type G (UK) power sockets: 250V x 3.15A* |
| Weight | 0.58kg |
| Materials | Alloy case, plastic insert |
| Warranty | 5 years |
| Certification | Fully tested / certified to BS 5733 & BS 1363-2, CE marked (meets BS 6396 requirements) |
| Boxed Dimensions | W450 x D70 x H60 mm |
| Boxed Weight | 0.64kg |
| Outer Box Dimensions - 10 units | W470 x D330 x H180 mm |
| Outer Box Weight | 6.6kg |
| *Conduction to the CCT 2 and the conduction of the CCT 2 and the conduction of the CCT 2 and the CCT | |

^{* 6} socket versions have no female GST 3-pole connector as six sockets is the maximum allowed from a single 13A wall socket (BS 6396). Six socket configurations are limited to 3.15A fuse.







Underdesk power module - Type G UPMA-6P1N



Features

Install in cable trays or fix to the underside of the desk with brackets or velcro pads provided

6 x Type G (UK) 3.15A individually fused power sockets*

1 x red neon master switch

1x male GST 3-pole connector*

1 - 10m metre mains power cables available with 13A Type G (UK) plug to GST 3-pole female connector

1 or 2 metre connector cable available with male to female GST 3-pole connectors

250mm trailing earth wire

Champagne alloy case with black plastic insert

| Module Dimensions | W430 x D52 x H48 mm |
|-----------------------------------------|-----------------------------------------------------------------------------------------|
| Capacitities | Type G (UK) power sockets: 250V x max. 3.15A* |
| Weight | 0.62kg |
| Materials | Alloy case, plastic insert |
| Warranty | 5 years |
| Certification | Fully tested / certified to BS 5733 & BS 1363-2, CE marked (meets BS 6396 requirements) |
| Boxed Dimensions | W510 x D70 x H60 mm |
| Boxed Weight | 0.69kg |
| Outer Box Dimensions - 10 units | W540 x D310 x H180 mm |
| Outer Box Weight | 7.1kg |
| *************************************** | |

^{* 6} socket versions have no female GST 3-pole connector as six sockets is the maximum allowed from a single 13A wall socket (BS 6396). Six socket configurations are limited to 3.15A fuse.







Underdesk power module - Type E UPMA-2P(E)



Features

Install in cable trays or fix to the underside of the desk with brackets or velcro pads provided

2 x Type E (French) power sockets

1 x male + 1 x female GST 3-pole connector

1 - 10m metre mains power cables available with 16A Type E (French) plug to GST 3-pole female connector

1 or 2 metre connector cable available with male to female GST 3-pole connectors

250mm trailing earth wire

Champagne alloy case with black plastic insert

| Module Dimensions | W205 x D54 x H50 mm |
|---------------------------------|-------------------------------------------------------------------------------------------------------|
| Capacitities | Type E (French) power sockets: 250V x 16A |
| Weight | 326g |
| Materials | Alloy case, plastic insert |
| Warranty | 5 years |
| Certification | IEC 60884-1:2002+A1:2006+A2:2013 NF C 61-314:2008+A1:2010 EN 62368-1:2014+A11:2017 CE marked |
| Boxed Dimensions | W280 x D70 x H60 mm |
| Boxed Weight | 0.37kg |
| Outer Box Dimensions - 10 units | |
| Outer Box Weight | 4.2kg |







Underdesk power module - Type E UPMA- 3P(E)



Features

Install in cable trays or fix to the underside of the desk with brackets or velcro pads provided

3 x Type E (French) power sockets

1x male + 1x female GST 3-pole connector

1 - 10m metre mains power cables available with 16A Type E (French) plug to GST 3-pole female connector

1 or 2 metre connector cable available with male to female GST 3-pole connectors

250mm trailing earth wire

Champagne alloy case with black plastic insert

| Module Dimensions | W248 x D54 x H50 mm |
|---------------------------------|-------------------------------------------------------------------------------------------------------|
| Capacitities | Type E (French) power sockets: 250V x 16A |
| Weight | 376g |
| Materials | Alloy case, plastic insert |
| Warranty | 5 years |
| Certification | IEC 60884-1:2002+A1:2006+A2:2013 NF C 61-314:2008+A1:2010 EN 62368-1:2014+A11:2017 CE marked |
| Boxed Dimensions | W280 x D70 x H60 mm |
| Boxed Weight | 0.42kg |
| Outer Box Dimensions - 10 units | |
| Outer Box Weight | 4.7kg |







Underdesk power module - Type E UPMA-4P(E)



Features

Install in cable trays or fix to the underside of the desk with brackets or velcro pads provided

4 x Type E (French) power sockets

1x male + 1x female GST 3-pole connector

1 - 10m metre mains power cables available with 16A Type E (French) plug to GST 3-pole female connector

1 or 2 metre connector cable available with male to female GST 3-pole connectors

250mm trailing earth wire

Champagne alloy case with black plastic insert

| Module Dimensions | W292 x D54 x H50 mm |
|---------------------------------|-------------------------------------------------------------------------------------------------------|
| Capacitities | Type E (French) power sockets: 250V x 16A |
| Weight | 425g |
| Materials | Alloy case, plastic insert |
| Warranty | 5 years |
| Certification | IEC 60884-1:2002+A1:2006+A2:2013 NF C 61-314:2008+A1:2010 EN 62368-1:2014+A11:2017 CE marked |
| Boxed Dimensions | W322 x D70 x H60 mm |
| Boxed Weight | 0.47kg |
| Outer Box Dimensions - 10 units | |
| Outer Box Weight | 5.2kg |







Underdesk power module - Type E UPMA-6P(E)



Features

Install in cable trays or fix to the underside of the desk with brackets or velcro pads provided

6 x Type E (French) power sockets

1 x male + 1 x female GST 3-pole connector

1 - 10m metre mains power cables available with 16A Type E (French) plug to GST 3-pole female connector

1 or 2 metre connector cable available with male to female GST 3-pole connectors

250mm trailing earth wire

Champagne alloy case with black plastic insert

| Module Dimensions | W334 x D54 x H50 mm |
|---------------------------------|-------------------------------------------------------------------------------------------------------|
| Capacitities | Type E (French) power sockets: 250V x 16A |
| Weight | 479g |
| Materials | Alloy case, plastic insert |
| Warranty | 5 years |
| Certification | IEC 60884-1:2002+A1:2006+A2:2013 NF C 61-314:2008+A1:2010 EN 62368-1:2014+A11:2017 CE marked |
| Boxed Dimensions | W420 x D70 x H60 mm |
| Boxed Weight | 0.54kg |
| Outer Box Dimensions - 10 units | |
| Outer Box Weight | 6kg |



