
Arc.

TA1_5

FOUR-LEG CHAIR SPECIFICATION

The Four-Leg Arc chair is a multipurpose product designed for conference rooms, seminar halls, education and modernised office spaces. Whatever its use, the Four-Leg is curated to add an extra level of support and comfort.

- Conforms to BS EN 1729: Part 1& 2 Strength, Stability and Ergonomics
- Fire Resistant
- Antimicrobial
- Lightweight and easy to move
- Stackable up to 10 high
- Easy to clean and tested for use with chlorine based cleaners
- 5 year guarantee



PRODUCT NAME FOUR-LEG COLOUR Marigold / Coral / Grape / Forest / Steel Blue / Anthracite MATERIAL PP1100 + 4% Glass Fibre BASE/FRAME MATERIAL Powder Coated Steel CERTIFICATIONS Conforms to BS EN 1729 Part 1 & 2 Antimicrobial FIRE RET LEVEL UL94 V-2 COMPONENT GUARANTEE S Years USAGE RECOMMENDED 8 Hours WEIGHT TOLERANCE 115kg GROSS WEIGHT N/A NETT WEIGHT 4.1kg BOXED VOLUME N/A		
COLOUR Marigold / Coral / Grape / Forest / Steel Blue / Anthracite MATERIAL PP1100 + 4% Glass Fibre BASE/FRAME MATERIAL Powder Coated Steel CERTIFICATIONS Conforms to BS EN 1729 Part 1 & 2 Antimicrobial FIRE RET LEVEL UL94 V-2 COMPONENT GUARANTEE USAGE RECOMMENDED 8 Hours WEIGHT TOLERANCE 115kg GROSS WEIGHT N/A NETT WEIGHT 4.1kg	SKU	TA1_5
Steel Blue / Anthracite MATERIAL PP1100 + 4% Glass Fibre BASE/FRAME MATERIAL Powder Coated Steel CERTIFICATIONS Conforms to BS EN 1729 Part 1 & 2 Antimicrobial FIRE RET LEVEL UL94 V-2 COMPONENT GUARANTEE 5 Years USAGE RECOMMENDED 8 Hours WEIGHT TOLERANCE 115kg GROSS WEIGHT N/A NETT WEIGHT 4.1kg	PRODUCT NAME	FOUR-LEG
MATERIAL PP1100 + 4% Glass Fibre BASE/FRAME MATERIAL Powder Coated Steel CERTIFICATIONS Conforms to BS EN 1729 Part 1 & 2 Antimicrobial FIRE RET LEVEL UL94 V-2 COMPONENT GUARANTEE 5 Years USAGE RECOMMENDED 8 Hours WEIGHT TOLERANCE 115kg GROSS WEIGHT N/A NETT WEIGHT 4.1kg	COLOUR	Marigold / Coral / Grape / Forest /
BASE/FRAME MATERIAL Powder Coated Steel CERTIFICATIONS Conforms to BS EN 1729 Part 1 & 2 Antimicrobial FIRE RET LEVEL UL94 V-2 COMPONENT GUARANTEE 5 Years USAGE RECOMMENDED 8 Hours WEIGHT TOLERANCE 115kg GROSS WEIGHT N/A NETT WEIGHT 4.1kg		Steel Blue / Anthracite
CERTIFICATIONS Conforms to BS EN 1729 Part 1 & 2 Antimicrobial FIRE RET LEVEL UL94 V-2 COMPONENT GUARANTEE 5 Years USAGE RECOMMENDED 8 Hours WEIGHT TOLERANCE 115kg GROSS WEIGHT N/A NETT WEIGHT 4.1kg	MATERIAL	PP1100 + 4% Glass Fibre
Antimicrobial FIRE RET LEVEL UL94 V-2 COMPONENT GUARANTEE 5 Years USAGE RECOMMENDED 8 Hours WEIGHT TOLERANCE 115kg GROSS WEIGHT N/A NETT WEIGHT 4.1kg	BASE/FRAME MATERIAL	Powder Coated Steel
Antimicrobial FIRE RET LEVEL UL94 V-2 COMPONENT GUARANTEE 5 Years USAGE RECOMMENDED 8 Hours WEIGHT TOLERANCE 115kg GROSS WEIGHT N/A NETT WEIGHT 4.1kg		
FIRE RET LEVEL COMPONENT GUARANTEE 5 Years USAGE RECOMMENDED 8 Hours WEIGHT TOLERANCE 115kg GROSS WEIGHT N/A NETT WEIGHT 4.1kg	CERTIFICATIONS	Conforms to BS EN 1729 Part 1 & 2
COMPONENT GUARANTEE 5 Years USAGE RECOMMENDED 8 Hours WEIGHT TOLERANCE 115kg GROSS WEIGHT N/A NETT WEIGHT 4.1kg		Antimicrobial
USAGE RECOMMENDED 8 Hours WEIGHT TOLERANCE 115kg GROSS WEIGHT N/A NETT WEIGHT 4.1kg	FIRE RET LEVEL	UL94 V-2
WEIGHT TOLERANCE 115kg GROSS WEIGHT N/A NETT WEIGHT 4.1kg	COMPONENT GUARANTEE	5 Years
GROSS WEIGHT N/A NETT WEIGHT 4.1kg	USAGE RECOMMENDED	8 Hours
NETT WEIGHT 4.1kg	WEIGHT TOLERANCE	115kg
NETT WEIGHT 4.1kg		
	GROSS WEIGHT	N/A
BOXED VOLUME N/A	NETT WEIGHT	4.1kg
	BOXED VOLUME	N/A
EFFECTIVE VOLUME N/A	EFFECTIVE VOLUME	N/A
BOXED WIDTH N/A	BOXED WIDTH	N/A
BOXED DEPTH N/A	BOXED DEPTH	N/A
BOXED HEIGHT N/A	BOXED HEIGHT	N/A







SHELL COLOURS



FRAME COLOURS



Black

PRODUCT WIDTH	485
PRODUCT DEPTH	520
PRODUCT HEIGHT	820
CHAIR SEAT HEIGHT	430
CHAIR SEAT WIDTH	425
CHAIR SEAT DEPTH	410
CHAIR BACK HEIGHT	425
CHAIR BACK WIDTH	405
MECHANISM TYPE	N/A
ANTI TILT MECHANISM	N/A
ARM TYPE	N/A
ARM HEIGHT	N/A
GAS LIFT COLOUR	N/A
GAS LIFT SIZE	N/A
CASTOR SIZE	N/A
FOOT TYPE	N/A
STACK QTY	10 High